



PELTOR™

FMT120 Rally Intercom

Features and Specifications



- The Peltor FMT120 intercom provides a full duplex connection with extremely high sound quality.
- The audio output (AUX) enables sound recording of the communication between driver and co-driver
- An attenuation switch to change the driver's microphone sensitivity, which is set 10 dB lower than the co-driver's as standard
- Separate volume controls for driver and co-driver
- LED indicator for On/Off and low battery
- EXT connection for mobile phone or communication radio
- Connection for push to talk (PTT) button
- Compatible with Peltor G78 rally helmet
- Possible to switch between dynamic and electret microphone

Accessories

- MT54N-13/1** Electret microphone
- FC16** Battery eliminator
- FL6U-**.** Flex cord for connecting a communication radio to the FMT120. Flex cords come in a range of versions depending on the type of radio.
- FL6U-28**
- FL6U-48** Flex cords for connecting a mobile phone to the FMT120. In most cases you will also need a small phone adapter, the TAH**.
- TK52** Large PTT button, 2.0 m cord.
- TK57-01/1** Small PTT button, 1.0 m cord

Technical Data Specifications

Power: Battery Type: 9V Alkaline battery or 12V power from car

Operating time: 10h with 9V battery

Weight: 354g (with 9V battery)
416g (with 9V battery, inner packaging and manual)

Operating temperature: -25 °C to +70 °C

Storage Temperature: -40 °C to +70 °C

Certification: CE EMC 89/336/EEG

Warranty: 2 years limited warranty (EMEA)

In the box: 1 x FMT120 intercom
1 x 9V battery
1 x Manual



- 1 AUX connection
- 2 Volume control driver
- 3 LED indicator
- 4 Volume control co-driver
- 5 PTT connection
- 6 EXT connection
- 7 Battery lid
- 8 Connection to headsets or helmets